8th FerryBox Workshop

#### Robust Sequential Injection Analyzer for autonomous Nutrient Analysis

D. Blandfort, C. Ahlers, Helmholtz-Zentrum Geesthacht, Institute of Coastal Research







Mission Objective and resulting Design Goals

"To construct a platform for the development of reliable, autonomous nutrient Analysers, usable on-board ships in ocean and river environments in liaison with the FerryBox-System"

- → Flexibility
- → Remote supervision and control
- → Low detection Limits

- → High Reliability
- → Low reagent consumption
- → High Sample Frequency



Implementation of Requirements and Design Goals

- → Flexibility
  - → 16-Port Valve
  - → Raspberry Pi; Python
- → Remote controllable
  - → Connectivity via Ethernet, W-Lan, Bluetooth, Serial, ...
- → Low detection Limits
  - $\rightarrow$  50 mm cuvette for NO<sub>x</sub>
  - → Hamamatsu Spectrometer

- → High Reliability
  - → Atmega Microcontroller
  - → Internal Error detection
- → Low reagent consumption
  - → Small diameter piping (0.25 mm)
  - → Smallest available diameter for cuvette
- → High Sample Frequency
  - → Hamamatsu Spectrometer

# Robust Sequential Injection Analyzer for autonomous Nutrient Analysis Drawbacks of the chosen Set-up





- → Material of sealing disk
- → Blocking due to small diameter
- → Cavitation effects
- → length of the cuvette



NOx Analyser | Limits | Experience | Outlook



#### **Reagent Consumption**

Puffer: 0.17 ml

Colour: 0.17 ml

Sample: 0.50 ml

 $NO_2$ 

Detection Limit: ~ 0.1 µmol/l

Duration: ~50 s

 $NO_3$ 

Detection Limit: ~ 1.9 µmol/l

Duration: ~ 10 min



PO4- Analyser | Limits | Experience | Outlook



#### **Reagent Consumption**

Acid: 0.20 ml

Colour 0.20 ml

Sample: 0.50 ml

 $PO_4$ 

Detection Limit: ~ 0.05 µmol/l

Duration: ~60 s